J-LAR®



CLEAR TO THE CORE SOLVENT-BASED ACRYLIC PACKAGING TAPE

TYPICAL APPLICATIONS

- For overlamination and label protection applications that demand a clear to the core tape
- Also used for light duty packaging, paper and book repair and mending, and holding applications
- Recommended for use with counter and desk dispensers

PRODUCT FEATURES

- · Glossy, brilliantly clear
- Will not yellow with age or discolor packages or objects after being applied
- Lightweight
- Easily dispensed from counter or desk dispensers
- Stronger than cellophane or acetate

CONSTRUCTION

Overall Grade/Function: Clear to the core packaging

Backing: Crystal clear, biaxially oriented polypropylene film (BOPP)

Adhesive: Crystal clear, solvent-based acrylic

STANDARD WIDTH(S)

½ in ¾ in 1 in

STANDARD LENGTH(S)

36 yd 72 yd

Contact your Shurtape sales representative for other available sizes

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)

CLEAR (CLR)

| Tensile Strength | 24 lbs/in width | 42.0 N /10 mm |
|-------------------------------|-----------------|----------------------|
| Adhesion to Stainless Steel | 30 oz/in width | 3.28 N/10 mm |
| Thickness | 2.6 mils | 0.066 mm |
| Elongation | 140% | 140% |
| Application Temperature Range | 20 F to 110 F | -7 C to 43 C |
| Service Temperature Range | -20 F to 180 F | -29 C to 82 C |
| | | |

PHYSICAL PROPERTIES STANDARD

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



METRIC