

P-665



PROFESSIONAL GRADE, GAFFER'S TAPE



TYPICAL APPLICATIONS

- For demanding applications that require clean removal in the audio/visual, television, photography, theatrical and motion picture industries, such as holding wiring, lighting and props

PRODUCT FEATURES

- High adhesion and tack
- Removes cleanly from most surfaces*
- Conformable
- Hand-tearable in machine and cross directions

CONSTRUCTION

Overall Grade/Function: Professional

Backing: Matte finish coated cloth

Adhesive: Synthetic rubber

STANDARD WIDTH(S)

48 mm 72 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

APPLICABLE STANDARDS

CID A-A-1586A

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Test tape on an inconspicuous area before using.

COLOR(S)



GRAY
(GRY)



WHITE
(WHI)

PHYSICAL PROPERTIES

Tensile Strength

50 lbs/in width

87.6 N/10 mm

Adhesion to Stainless Steel

80 oz/in width

8.76 N/10 mm

Thickness

11.5 mils

0.29 mm

Elongation

4%

4%

Service Temperature Range

50 F to 180 F

10 C to 82 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

